


GAS APPROVED BALL VALVE

Lever Handle FI X FI Extended Spindle

Product Specifications



Specifications

Working temperature -20°C to 120°C
Maximum pressure rating 2100kPa

Sizing Chart (MM)

	L1	L2	H1	H2	H2	W	TH
EXTG15F	58	101	105	64.6	101	30	Rp 1/2"
EXTG20F	66	101	112	64.6	104	37	Rp 3/4"
EXTG25F	81	101	121	64.6	108	46	Rp 1"
EXTG32F	91	140	136	66.2	127	58	Rp 1 1/4"
EXTG40F	102	140	147	66.2	132	69	Rp 1 1/2"
EXTG50F	121	140	163	66.2	141	84	Rp 2"
EXTG65F	150	232	226	97.5	193	108	Rp 2 1/2"
EXTG80F	177	232	248	97.5	204	130	Rp 3"
EXTG100F	212	232	277	97.5	218	160	Rp 4"

Features

- AGA approved
- Full bore
- 100% pressure tested
- Available in sizes 15mm (1/2") to 100mm (4")
- Blow proof spindle
- Extended Spindle
- Stainless Steel handle
- Tested and certified to AS 4617

Material Chart

Part	Material
Body	Brass
Cap	Brass
Ball	Stainless Steel
Spindle	Stainless Steel
Seal	PTFE
O Rings	HNBR
Handle	Stainless Steel
Spindle Extension	Brass
Handle Extension	Brass

For more information on Logi Valve, contact:
Austworld 15 Activity Crescent, Molendinar, Queensland 4214 Australia
P. 1300 780 430 F. 1300 780 441 E. info@austworld.com.au

Austworld Pty Ltd. All rights reserved 2018. Austworld and Logi Valve are registered trade mark belonging to Austworld Pty Ltd.

Revision no. 1.1 | 11/03/2024

